

# Guaranteed Cost Controller Design of Networked Control Systems with State Delay

XIE Jin-Song<sup>1</sup> FAN Bing-Quan<sup>1</sup> Young Sam Lee<sup>2</sup> YANG Jin<sup>3</sup>

**Abstract** This paper is concerned with the state-feedback guaranteed cost controller design for a class of networked control systems (NCSs) with state-delay. A new model of the NCSs is provided under consideration of the network-induced delay. A sufficient condition for the existence of a guaranteed cost controller for NCSs is presented by a set of linear matrix inequalities (LMIs). A method, which can transform non-convex to the convex, is applied. Accordingly, a numerical algorithm is proposed to obtain the lower bound. Theoretical analysis through an example shows the effectiveness of the method.

**Key words** Networked control systems, guaranteed cost control, linear matrix inequalities

## 1 Introduction

The networked control systems (NCSs) have recently been studied by more and more researchers since their low cost, reduced weight and power requirements, simple installation and maintenance and high reliability<sup>[1,2]</sup>. In an NCS, one of the important issues to treat is the effect of the network-induced delay on the system performance. For the NCSs with different scheduling protocols, the network-induced delay may be constant, time-varying, or even random variable<sup>[3]</sup>.

The guaranteed cost control of uncertain systems was first put forward by [4] and studied by a lot of researchers, which is to design a controller to robustly stabilize the uncertain system and guarantee an adequate level of performance. The guaranteed cost control approach has recently been extended to the uncertain time-delay systems, for the state feedback cases, see [5~7]; for the output feedback case, see [8].

In this paper, the author's intention is to design a guaranteed cost controller based on the network delay for a class of uncertain time-delay. Sufficient condition for the existence of a guaranteed cost state-feedback controller is established in terms of matrix inequalities. At the same time, the maximum allowable value  $\tau_{max}$  of the network-induced and guaranteed cost bound are obtained and the guaranteed cost control strategy is proven by a numerical example.

The remainder of this paper is organized as follows: Section 2 describes the problem formulation. In Section 3, details of the modeling of networked control systems are discussed. Section 4 obtains the guaranteed cost controller design and illuminates the method which switches a non-convex problem to a convex. Section 5 introduces a numerical example. Section 6 presents conclusions.

## 2 Problem formulation

Consider a class of linear uncertain system with time-delay in the state described by the following equations

$$\begin{cases} x'(t) = [A + \Delta A]x(t) + [A_d + \Delta A_d]x(t-d) + \\ \quad [B + \Delta B]u(t) \\ x(t) = \varphi(t), t \in [-d, 0] \end{cases} \quad (1)$$

Received April 12, 2005; in revised form February 27, 2006  
Supported by National Natural Science Foundation of P. R. China (70371011), Shanghai Leading Academic Discipline Project (T0502)  
1. Center of Research on Transports System, University of Shanghai for Science & Technology, Shanghai 200093, P. R. China 2. School of Electrical Engineering, Inha University, Incheon, Korea 3. College of Science, University of Shanghai for Science & Technology, Shanghai 200093, P. R. China  
DOI: 10.1360/aas-007-0170

where  $x(t) \in R^n$  is the state vector,  $u(t) \in R^m$  is the control input vector,  $A, A_d \in R^{n \times n}$  and  $B \in R^{n \times m}$  are known constant real matrices,  $\Delta A, \Delta A_d$  and  $\Delta B$  are matrix-valued functions of appropriate dimension parameter uncertainties in the system model.  $\varphi(t)$  is a given continuous vector-valued initial function and subsection differential on  $[-d, 0]$ . The parameter uncertainties considered are assumed to be norm bounded and satisfy

$$[\Delta A \quad \Delta A_d \quad \Delta B] = DF(t)[E \quad E_d \quad E_b] \quad (2)$$

where  $D, E, E_d, E_b$  are known constant real matrices of appropriate dimensions that represent the structure of uncertainties, and  $F(t) \in R^{i \times j}$  is an uncertain matrix function with Lebesgue measurable elements and satisfies

$$F^T(t)F(t) \leq I \quad (3)$$

in which  $I$  denotes the identity matrix of appropriate dimension. Associated with system (1) is the cost function

$$J = \int_0^\infty [x^T(t)Qx(t) + u^T(t)Ru(t)]dt \quad (4)$$

where  $Q$  and  $R$  are given positive-definite symmetric matrices.

**Definition**<sup>[9]</sup>. For the uncertain system (1), if there exist a control law  $u^*(t)$  and a positive scalar  $J^*$  such that for all admissible uncertainties the closed-loop system is stable and the closed-loop value of the cost function (4) satisfies  $J \leq J^*$ , then  $J^*$  is said to be a guaranteed cost and  $u^*(t)$  is said to be a guaranteed cost control law for the uncertain system (1).

The objective of this paper is to develop a procedure for designing a memoryless state feedback guaranteed cost control law

$$u(t) = Kx(t) \quad (5)$$

for the linear uncertain time-delay system (1).

## 3 Modeling of networked control systems

In an NCS, suppose that the sensor is clock-driven, the controller and actuator are event-driven and the data is transmitted with a single-packet. Then the real input  $u(t)$  realized through zero-order hold in (1) is a piecewise constant function. Furthermore, if we consider the effect of the network-induced delay and network packet dropout on the NCSs, then the real control system (1) with (5) can be rewritten as

$$\begin{cases} x'(t) = [A + \Delta A]x(t) + [A_d + \Delta A_d]x(t-d) + \\ \quad [B + \Delta B]u(t), t \in [i_k h + \tau_k, i_{k+1} h + \tau_{k+1}) \\ u(t) = Kx(t - \tau_k), t \in \{i_k h + \tau_k, \dots\} \end{cases} \quad (6)$$

where  $h$  is the sampling period,  $i_k (k = 1, 2, \dots)$  are some integers and  $\{i_1, i_2, \dots\} \subseteq \{1, 2, \dots\}$ ,  $\tau_k$  is the time delay, which denotes the time from the instant  $i_k h$  when the sensor nodes sample sensor data from a plant to the instant when actuators transfer data to the plant. Obviously,  $\bigcup_{k=1}^{\infty} [i_k h + \tau_k, i_{k+1} h + \tau_{k+1}] = [0, \infty)$ . According to (2), system (6) can be rewritten as the following equivalent form

$$x'(t) = [A + DF(t)E]x(t) + [A_d + DF(t)E_d]x(t-d) + [B + DF(t)E_b]Kx(i_k h), t \in [i_k h + \tau_k, i_{k+1} h + \tau_{k+1}) \quad (7)$$

and (4) can be rewritten as

$$J = \int_0^{\infty} x^T(t)Qx(t)dt + \sum_{k=1}^{\infty} \int_{i_k h + \tau_k}^{i_{k+1} h + \tau_{k+1}} x^T(i_k h)K^T R K x(i_k h)dt \quad (8)$$

## 4 Main results

The following Lemmas will be used.

**Lemma 1.** For any vectors  $a, b$  and positive-definite matrix  $X$ , there exists

$$\pm 2a^T b \leq a^T X^{-1} a + b^T X b$$

**Lemma 2.** Given appropriate dimension matrices  $D, E$  and symmetric  $Y$ , the matrix inequality

$$Y + DFE + E^T F^T D^T < 0$$

holds for all  $F$  satisfying  $F^T F \leq I$  if and only if there exists a constant  $\varepsilon > 0$  such that

$$Y + \varepsilon DD^T + \varepsilon^{-1} E^T E < 0$$

First we present a sufficient condition for the existence of memoryless state feedback guaranteed cost control laws for an uncertain time-delay system.

**Theorem 1.**  $u(t) = Kx(t)$ , ( $K = YX^{-T}$ ) is a guaranteed cost controller if there exist symmetric positive-definite matrices  $\bar{P} > 0, \bar{S} > 0, \bar{T} > 0$ , and appropriate dimension matrices  $X, Y, \bar{N}_i (i = 1, 2, 3, 4)$ , and a scalar  $\varepsilon > 0$  for any given scalars  $\tau, \rho_i (i = 2, 3, 4)$ , and matrices  $Q > 0, R > 0$  such that (9) holds. At the same time the guaranteed cost  $J^*$  satisfies (11).

$$(i_{k+1} - i_k)h + \tau_{k+1} \leq \tau, k = 1, 2, \dots \quad (10)$$

$$J \leq \varphi^T(0)X^{-1}\bar{P}X^{-T}\varphi(0) + \int_{-d}^0 \varphi^T(\alpha)X^{-1}\bar{S}X^{-T}\varphi(\alpha)d\alpha + \int_0^{\tau} \int_{-\beta}^0 \varphi'^T(\alpha)X^{-1}\bar{T}X^{-T}\varphi'(\alpha)d\alpha d\beta = J^* \quad (11)$$

where

$$\begin{cases} \Omega_{11} = \bar{S} + \bar{N}_1 + \bar{N}_1^T - AX^T - XA^T + \varepsilon DD^T \\ \Omega_{21} = \bar{N}_2 - XA_d^T - \rho_2 AX^T + \varepsilon \rho_2 DD^T \\ \Omega_{22} = -\bar{S} - \rho_2 XA_d^T - \rho_2 A_d X^T + \varepsilon \rho_2^2 DD^T \\ \Omega_{31} = -\bar{N}_1^T + \bar{N}_3 - Y^T B^T - \rho_3 AX^T + \varepsilon \rho_3 DD^T \\ \Omega_{32} = -\bar{N}_2^T - \rho_2 Y^T B^T - \rho_3 A_d X^T + \varepsilon \rho_2 \rho_3 DD^T \\ \Omega_{33} = -\bar{N}_3 - \bar{N}_3^T - \rho_3 BY - \rho_3 Y^T B^T + \varepsilon \rho_3^2 DD^T \\ \Omega_{41} = \bar{N}_4 + X - \rho_4 AX^T + \bar{P} + \varepsilon \rho_4 DD^T \\ \Omega_{42} = \rho_2 X - \rho_4 A_d X^T + \varepsilon \rho_2 \rho_4 DD^T \\ \Omega_{43} = -\bar{N}_4 + \rho_3 X - \rho_4 BY + \varepsilon \rho_3 \rho_4 DD^T \\ \Omega_{44} = \tau \bar{T} + \rho_4 X + \rho_4 X^T + \varepsilon \rho_4^2 DD^T \end{cases}$$

**Proof.** Construct a Lyapunov functional as

$$V(t) = x^T(t)Px(t) + \int_{-d}^t x^T(\alpha)Sx(\alpha)d\alpha + \int_0^{\tau} \int_{-\beta}^t x'^T(\alpha)Tx'(\alpha)d\alpha d\beta \quad (12)$$

where  $P > 0, S > 0, T > 0$ .

Since  $x(t) - x(i_k h) - \int_{i_k h}^t x'(\alpha)d\alpha = 0$  and by (7), one can see that any arbitrary matrices  $N_i, M_i (i = 1, 2, 3, 4)$  of appropriate dimensions satisfy

$$2[x^T(t)N_1 + x^T(t-d)N_2 + x^T(i_k h)N_3 + x^T(t)N_4] \times [x(t) - x(i_k h) - \int_{i_k h}^t x'(\alpha)d\alpha] = 0 \quad (13)$$

$$2[x^T(t)M_1 + x^T(t-d)M_2 + x^T(i_k h)M_3 + x'^T(t)M_4] \times [-\bar{A}x(t) - \bar{A}_d x(i_k h) - \bar{B}Kx(i_k h) + x'(t)] = 0 \quad (14)$$

where  $\bar{A} = A + DF(t)E, \bar{A}_d = A_d + DF(t)E_d, \bar{B} = B + DF(t)E_b$ .

Taking the time derivative of  $V(t)$  for  $t \in [i_k h + \tau_k, i_{k+1} h + \tau_{k+1})$ , and using (13) and (14) yields

$$\begin{aligned} V'(t) &= 2x^T(t)Px'(t) + x^T(t)Sx(t) + \tau x'^T(t)Tx'(t) - \\ &\quad x^T(t-d)Sx(t-d) - \int_{-\tau}^t x'^T(\alpha)Tx'(\alpha)d\alpha + \\ &\quad 2[x^T(t)N_1 + x^T(t-d)N_2 + x^T(i_k h)N_3 + x'^T(t)N_4] \times \\ &\quad [x(t) - x(i_k h) - \int_{i_k h}^t x'(\alpha)d\alpha] + \\ &\quad 2[x^T(t)M_1 + x^T(t-d)M_2 + x^T(i_k h)M_3 + x'^T(t)M_4] \times \\ &\quad [-\bar{A}x(t) - \bar{A}_d x(i_k h) - \bar{B}Kx(i_k h) + x'(t)] \end{aligned} \quad (15)$$

$$\Omega = \begin{bmatrix} \Omega_{11} & * & * & * & * & * & * & * \\ \Omega_{21} & \Omega_{22} & * & * & * & * & * & * \\ \Omega_{31} & \Omega_{32} & \Omega_{33} & * & * & * & * & * \\ \Omega_{41} & \Omega_{42} & \Omega_{43} & \Omega_{44} & * & * & * & * \\ \tau \bar{N}_1^T & \tau \bar{N}_2^T & \tau \bar{N}_3^T & \tau \bar{N}_4^T & -\tau \bar{T} & * & * & * \\ 0 & 0 & Y & 0 & 0 & -R^{-1} & * & * \\ X^T & 0 & 0 & 0 & 0 & 0 & -Q^{-1} & * \\ EX^T & E_d X^T & E_b X^T & 0 & 0 & 0 & 0 & -\varepsilon I \end{bmatrix} < 0 \quad (9)$$

From (10) it can be seen that when  
 $t \in [i_k h + \tau_k, i_{k+1} h + \tau_{k+1})$

$$-\int_{t-\tau}^t x'(\alpha) T x'(\alpha) d\alpha \leq -\int_{i_k h}^t x'(\alpha) T x'(\alpha) d\alpha \quad (16)$$

Using Lemma 1, we can show that

$$-2[x^T(t)N_1 + x^T(t-d)N_2 + x^T(i_k h)N_3 + x^T(t)N_4] \times \\ \int_{i_k h}^t x'(\alpha) d\alpha \leq \tau e^T(t) N T^{-1} N^T e(t) + \int_{i_k h}^t x'^T(\alpha) T x'(\alpha) d\alpha \quad (17)$$

where

$$e^T(t) = [x^T(t) \quad x^T(t-d) \quad x^T(i_k h) \quad x^T(t)]$$

$$N^T = [N_1^T \quad N_2^T \quad N_3^T \quad N_4^T]$$

Combining (15), (16) and (17), we obtain

$$V'(t) \leq e^T(t) \bar{\Omega} e(t) - x^T(t) Q x(t) - \\ x^T(i_k h) K^T R K x(i_k h) \quad (18)$$

where

$$\bar{\Omega} = \begin{bmatrix} \bar{\Omega}_{11} & * & * & * & * \\ \bar{\Omega}_{21} & \bar{\Omega}_{22} & * & * & * \\ \bar{\Omega}_{31} & \bar{\Omega}_{32} & \bar{\Omega}_{33} & * & * \\ \bar{\Omega}_{41} & \bar{\Omega}_{42} & \bar{\Omega}_{43} & \bar{\Omega}_{44} & * \\ \tau N_1^T & \tau N_2^T & \tau N_3^T & \tau N_4^T & -\tau T \end{bmatrix}$$

$$\begin{cases} \bar{\Omega}_{11} = S + N_1 + N_1^T - M_1 \bar{A} - \bar{A}^T M_1^T + Q \\ \bar{\Omega}_{21} = N_2 - M_2 \bar{A} - \bar{A}_d^T M_1^T \\ \bar{\Omega}_{22} = -S - M_2 \bar{A}_d - \bar{A}_d^T M_2^T \\ \bar{\Omega}_{31} = -N_1^T + N_3 - K^T \bar{B}^T M_1^T - M_3 \bar{A} \\ \bar{\Omega}_{32} = -N_2^T - K^T \bar{B}^T M_2^T - M_3 \bar{A}_d \\ \bar{\Omega}_{33} = -N_3 - N_3^T - M_3 \bar{B} K - K^T \bar{B}^T M_3^T + K^T R K \\ \bar{\Omega}_{41} = N_4 + M_1^T - M_4 \bar{A} + P \\ \bar{\Omega}_{42} = M_2^T - M_4 \bar{A}_d \\ \bar{\Omega}_{43} = -N_4 + M_3^T - M_4 \bar{B} K \\ \bar{\Omega}_{44} = \tau T + M_4 + M_4^T \end{cases}$$

So if  $\bar{\Omega} < 0$ , then (18) implies  $V'(t) < 0$ .

Using Lemma 2, we obtain

$$\bar{\Omega} = \bar{Y} + M_d^T F M_e + M_e^T F M_d < 0 \\ \Leftrightarrow \bar{Y} + \varepsilon M_d^T M_d + \varepsilon^{-1} M_e^T M_e < 0 \quad (19)$$

where

$$\bar{Y} = \begin{bmatrix} \bar{Y}_{11} & * & * & * & * \\ \bar{Y}_{21} & \bar{Y}_{22} & * & * & * \\ \bar{Y}_{31} & \bar{Y}_{32} & \bar{Y}_{33} & * & * \\ \bar{Y}_{41} & \bar{Y}_{42} & \bar{Y}_{43} & \bar{Y}_{44} & * \\ \tau N_1^T & \tau N_2^T & \tau N_3^T & \tau N_4^T & -\tau T \end{bmatrix}$$

$$\begin{cases} \bar{Y}_{11} = S + N_1 + N_1^T - M_1 A - A^T M_1^T + Q \\ \bar{Y}_{21} = N_2 - M_2 A - A_d^T M_1^T \\ \bar{Y}_{22} = -S - M_2 A_d - A_d^T M_2^T \\ \bar{Y}_{31} = -N_1^T + N_3 - K^T B^T M_1^T - M_3 A \\ \bar{Y}_{32} = -N_2^T - K^T B^T M_2^T - M_3 A_d \\ \bar{Y}_{33} = -N_3 - N_3^T - M_3 B K - K^T B^T M_3^T + K^T R K \\ \bar{Y}_{41} = N_4 + M_1^T - M_4 A + P \\ \bar{Y}_{42} = M_2^T - M_4 A_d \\ \bar{Y}_{43} = -N_4 + M_3^T - M_4 B K \\ \bar{Y}_{44} = \tau T + M_4 + M_4^T \\ M_d = -[(M_1 D)^T \quad (M_2 D)^T \quad (M_3 D)^T \quad (M_4 D)^T \quad 0] \\ M_e = [E \quad E_d \quad E_b K \quad 0 \quad 0] \end{cases}$$

In the sequel, by using Schur complement and defining:  $M = M_1, M_2 = \rho_2 M_1, M_3 = \rho_3 M_1, M_4 = \rho_4 M_1, X = M^{-1}, Y = K X^T, \bar{P} = X P X^T, \bar{S} = X S X^T, \bar{T} = X T X^T, \bar{N}_i = X N_i X^T (i = 1, 2, 3, 4)$ , and pre-, post-multiplying both sides with  $\text{diag}(X \quad X \quad X \quad X \quad X \quad I \quad I \quad I)$  and its transpose, we have (19)  $\Leftrightarrow \Omega < 0$ , thus proof of  $V'(t) < 0$ .

From (18) we can see

$$x^T(t) Q x(t) + x^T(i_k h) K^T R K x(i_k h) < -V'(t) \quad (20)$$

integrating (20) from  $i_k h + \tau_k$  to  $i_{k+1} h + \tau_{k+1}$ , and using  $\bigcup_{k=1}^{\infty} [i_k h + \tau_k, i_{k+1} h + \tau_{k+1}) = [0, \infty), V(\infty) = 0$  then we get the (11). Thus we complete the proof of Theorem 1.  $\square$

Given  $d$ , in order to obtain a controller  $u(t) = Y X^{-T} x(t)$ , which achieves the least guaranteed cost value  $J^*$ , we have to solve the following minimization problem

$$\text{Minimize } J_1 + J_2 + J_3 \text{ subject to (9)} \quad (21)$$

where

$$J_1 = \varphi^T(0) X^{-1} \bar{P} X^{-T} \varphi(0) \\ J_2 = \int_{-d}^0 \varphi^T(\alpha) X^{-1} \bar{S} X^{-T} \varphi(\alpha) d\alpha \\ J_3 = \int_0^\tau \int_{-\beta}^0 \varphi'^T(\alpha) X^{-1} \bar{T} X^{-T} \varphi'(\alpha) d\alpha d\beta \quad (22)$$

However, it is noted that the terms  $J_1, J_2, J_3$  are not convex functions of  $X$  and  $\bar{P}, \bar{S}, \bar{T}$ . As a result, unfortunately, we can not find in general the global minimum of the above minimization problem using a convex optimization algorithm<sup>[10]</sup>. However if we can afford more computational efforts, we can obtain a guaranteed cost controller achieving a suboptimal guaranteed cost, say  $J_{so}^*$ , using an iterative algorithm presented in [11].

In the sequel, let us derive the upper bounds on the cost functions  $J_1, J_2, J_3$ . Before starting the problem, let us define matrix values  $\Pi_1, \Pi_2, \Pi_3$ , such that

$$\Pi_1 = \varphi(0) \varphi^T(0) \\ \Pi_2 = \int_{-d}^0 \varphi(\alpha) \varphi^T(\alpha) d\alpha \\ \Pi_3 = \int_0^\tau \int_{-\beta}^0 \varphi'(\alpha) \varphi'^T(\alpha) d\alpha d\beta \quad (23)$$

To derive the upper bound on  $J_1$ , let us introduce a new variable  $\Lambda = \Lambda^T$  such that

$$X^{-1} \bar{P} X^{-T} < \Lambda \quad (24)$$

By Schur complement, (24) is equivalent to

$$\begin{bmatrix} -\Lambda & X^{-1} \\ X^{-T} & -\bar{P}^{-1} \end{bmatrix} < 0 \quad (25)$$

By introducing new values  $M, \bar{P}$ , the condition (25) can be replaced by

$$\begin{bmatrix} -\Lambda & M \\ M^T & -\bar{P} \end{bmatrix} < 0, M = X^{-1}, \bar{P} = \bar{P}^{-1} \quad (26)$$

Assuming (26), we can conclude that the following inequality holds

$$\varphi^T(0)X^{-1}\bar{P}X^{-T}\varphi(0) < \text{tr}(\Pi_1\Lambda) \quad (27)$$

To derive the upper bound on  $J_2$ , let us introduce a new variable  $\Pi = \Pi^T$  such that

$$X^{-1}\bar{S}X^{-T} < \Pi \quad (28)$$

By Schur complement, (28) is equivalent to

$$\begin{bmatrix} -\Pi & X^{-1} \\ X^{-T} & -\bar{S}^{-1} \end{bmatrix} < 0 \quad (29)$$

By introducing a new value  $\bar{S}$ , the condition (29) can be replaced by

$$\begin{bmatrix} -\Pi & M \\ M^T & -\bar{S} \end{bmatrix} < 0, \bar{S} = \bar{S}^{-1} \quad (30)$$

Assuming (30), we can conclude that the following inequality holds

$$\int_{-d}^0 \varphi^T(\alpha)X^{-1}\bar{S}X^{-T}\varphi(\alpha)d\alpha < \text{tr}(\Pi_2\Pi) \quad (31)$$

To derive the upper bound on  $J_3$ , let us introduce a new variable  $\Xi = \Xi^T$  such that

$$X^{-1}\bar{T}X^{-T} < \Xi \quad (32)$$

By Schur complement, (32) is equivalent to

$$\begin{bmatrix} -\Xi & X^{-1} \\ X^{-T} & -\bar{T}^{-1} \end{bmatrix} < 0 \quad (33)$$

By introducing a new value  $\bar{T}$ , the condition (33) can be replaced by

$$\begin{bmatrix} -\Xi & M \\ M^T & -\bar{T} \end{bmatrix} < 0, \bar{T} = \bar{T}^{-1} \quad (34)$$

Assuming (34), we can conclude that the following inequality holds

$$\int_0^\tau \int_{-\beta}^0 \varphi'^T(\alpha)X^{-1}\bar{T}X^{-T}\varphi'(\alpha)d\alpha d\beta < \text{tr}(\Pi_3\Xi) \quad (35)$$

For some constant  $J$ , assume

$$\text{tr}(\Pi_1\Lambda) + \text{tr}(\Pi_2\Pi) + \text{tr}(\Pi_3\Xi) < J \quad (36)$$

Combining these facts, we can construct a feasibility problem as follows

Find  $\bar{P}, \bar{S}, \bar{T}, X, \bar{P}, \bar{S}, \bar{T}, M, \Lambda, \Pi, \Xi, Y, \bar{N}_i (i = 1, 2, 3, 4), \varepsilon$   
Subject to  $\bar{P} > 0, \bar{S} > 0, \bar{T} > 0, (9)(26)(30)(34)(36)$

(37)

Given  $d$  and  $J$ , if the above problem has a solution, we can say that there exists a controller  $u(t) = YX^{-T}x(t)$  which guarantees the cost function (4) is less than  $J^*$ . Note that the conditions (26) (30) (34) still include nonlinear condition, eg.  $\bar{P} = \bar{P}^{-1}$ . However, using the idea in a cone complementary linearization algorithm<sup>[11]</sup>, the above feasibility problem can be solved iteratively. Now, we suggest the following nonlinear minimization problem involving LMI conditions instead of the original non-convex minimization problem in (21)

$$\begin{aligned} & \text{Minimize } \text{tr}(\bar{P}\bar{P} + \bar{S}\bar{S} + \bar{T}\bar{T} + XM) \\ & \text{Subject to } \bar{P} > 0, \bar{S} > 0, \bar{T} > 0, (9)(36) \\ & \begin{bmatrix} -\Lambda & M \\ M^T & -\bar{P} \end{bmatrix} < 0, \begin{bmatrix} -\Pi & M \\ M^T & -\bar{S} \end{bmatrix} < 0 \\ & \begin{bmatrix} -\Xi & M \\ M^T & -\bar{T} \end{bmatrix} < 0, \begin{bmatrix} \bar{P} & I \\ I & \bar{P} \end{bmatrix} \geq 0 \\ & \begin{bmatrix} \bar{S} & I \\ I & \bar{S} \end{bmatrix} \geq 0, \begin{bmatrix} \bar{T} & I \\ I & \bar{T} \end{bmatrix} \geq 0 \\ & \begin{bmatrix} X & I \\ I & M \end{bmatrix} \geq 0 \end{aligned} \quad (38)$$

If the solution of the above minimization problem is  $4n$ , that is,  $\text{tr}(\bar{P}\bar{P} + \bar{S}\bar{S} + \bar{T}\bar{T} + XM) = 4n^{[11]}$ , we can say from Theorem1 that the system (6) with the controller  $u(t) = YX^{-T}x(t)$  is uniformly asymptotically stable with the guaranteed cost  $J^*$ . Although it is still impossible to always find the globally optimal solution, the proposed nonlinear optimization problem is easier to solve than the original non-convex minimization problem in (21). Actually, utilizing the linearization method in [11], we can easily find a suboptimal minimum of the guaranteed cost using an iterative algorithm presented in the following.

#### Algorithm.

**Step 1.** Choose a sufficiently large initial  $J$  such that there exists a feasible solution in (38). Set  $J_{so} = J$ .

**Step 2.** Find a feasible set  $(\bar{P}_0, \bar{P}_0, \bar{S}_0, \bar{S}_0, \bar{T}_0, \bar{T}_0, X_0, M_0)$  satisfying LMIs in (38). Set  $k=1$ .

**Step 3.** Solve the following LMI problem for the variables  $(\bar{P}, \bar{P}, \bar{S}, \bar{S}, \bar{T}, \bar{T}, X, M)$ :

Minimize  $\text{tr}(\bar{P}_k\bar{P} + \bar{S}_k\bar{S} + \bar{T}_k\bar{T} + X_kM + \bar{P}\bar{P}_k + \bar{S}\bar{S}_k + \bar{T}\bar{T}_k + XM_k)$  subject to LMIs in (38).

Set  $\bar{P}_{k+1} = \bar{P}, \bar{S}_{k+1} = \bar{S}, \bar{T}_{k+1} = \bar{T}, X_{k+1} = X, \bar{P}_{k+1} = \bar{P}, \bar{S}_{k+1} = \bar{S}, \bar{T}_{k+1} = \bar{T}, M_{k+1} = M$ .

**Step 4.** If the condition (24), (28) and (32) are all satisfied, then set  $J_{so} = J$  and return to Step 2 after decreasing  $J$  to some extent. If the condition (24), (28) and (32) are not satisfied within a specified number of iterations, say  $k_{max}$ , then exit. Otherwise set  $k = k + 1$  and go to Step 3.

## 5 Numerical example

**Example.** Consider the following uncertain time-delay system:

$$x'(t) = \begin{bmatrix} 1 + 0.33F(t) & 0.42F(t) \\ 0.53F(t) & -2 + 0.67F(t) \end{bmatrix} x(t) +$$

$$\begin{bmatrix} 0.5 & 0.32 \\ 0 & -0.5 \end{bmatrix} x(t-d) + \begin{bmatrix} 0.47 \\ 0.75 \end{bmatrix} u(t)$$

where  $d = 1, x_1(t) = 3e^{t+1} - 1, x_2(t) = 0$ , for  $t \in [-1, 0]$

and  $F^2(t) \leq 1$ . We consider the cost function (11), set  $Q = 0.5I$ ,  $R = 0.1$ ,  $\rho_2 = 2$ ,  $\rho_3 = 3$ ,  $\rho_4 = 4$  and use the algorithm in the above, then obtain Table 1 with  $d$  given.

From Table 1: when  $d$  declines a little, the maximum allowable value  $\tau_{max}$  of the network-induced increases a lot, even so, the system will be asymptotically stable as before. Accordingly, the value  $J_{so}$  drops a lot. Of course, we can give  $Q, R, \rho_2, \rho_3, \rho_4$  other values, relative  $\tau_{max}, J_{so}, K$  will be obtained respectively.

Table 1 When  $d$  given then obtaining  $\tau_{max}, J_{so}, K$

$d$	$\tau_{max}$	$J_{so}$	$K$
1	0.15	469.98	[-2.690 -1.096]
0.5	0.45	126.63	[-1.295 0.120]

## 6 Conclusion

In this paper, we firstly model NCSs with network delay for a class of uncertain time-delay systems. Based on the model, a guaranteed cost controller design is presented and a sufficient condition for the existence of a guaranteed cost state-feedback for a class of uncertain time-delay systems is given and an algorithm involving a convex optimization is applied to construct a controller with a suboptimal guaranteed cost such that the system can be stabilized for all admissible uncertainties. At the same time a simulated example is given to show the effectiveness of the algorithm.

### References

- Walsh G C, Ye H. Scheduling of networked control systems. *IEEE Control Systems Magazine*, 2001, **21**(1): 57~65
- Walsh G C, Ye H, Bushnell L G. Stability analysis of networked control systems. *IEEE Transactions on Control Systems Technology*, 2002, **10**(3): 438~446
- Zhang W, Branicky M S, Phillips S M. Stability of networked control systems. *IEEE Control Systems Magazine*, 2001, **21**(1): 84~99
- Chang S S L, Peng T K C. Adaptive guaranteed cost control of systems with uncertain parameters. *IEEE Transactions on Automatica Control*, 1972, **17**(4): 474~483
- Petersen I R, McFarlane D C. Optimal guaranteed cost control and filtering for uncertain linear system. *IEEE Transactions on Automatica Control*, 1994, **39**(9): 1971~1977
- Yu L, Chu J. An LMI approach to guaranteed cost control of linear uncertain time-delay systems. *Automatica*, 1999, **35**(6): 1155~1159
- Mahmoud M S. Control of uncertain state-delay systems: guaranteed cost approach. *IMA Journal of Mathematical Control and Information*, 2001, **18**(1): 109~128
- Esfahani S H, Petersen I R. An LMI approach to the output-feedback guaranteed cost control for uncertain time-delay systems. In: Proceedings of the 37th IEEE Conference on Decision and Control, 1998, **2**: 1358~1363
- Nian X, Feng J. Guaranteed cost control of a linear uncertain system with multiple time-varying delay: an LMI approach. *IEEE Proceedings: Control Theory and Applications*, 2003, **150**: 17~21
- Ghaoui L E, Oustry F, AitRami M. A cone complementarity linearization algorithm for static output-feedback and related problems. In: Proceeding of the American Control Conference Arlington, 1997. **42**(8): 1171~1176
- Young Sam Lee, Young Soo Moon, Wook Hyun Kwon. Delay-dependent guaranteed cost control for uncertain state-delayed systems. In: Proceedings of American Control Conference, 2001, **5**: 3376~3381



**XIE Jin-Song** Received his B.S. and M.S. degrees from Nanjing Normal University in 1996 and 2005, respectively. Now he is a Ph.D. candidate of the College of Management, University of Shanghai for Science & Technology. His research interests include transportation system engineering, transportation planning, and intelligent transportation systems. Corresponding author of this paper. E-mail: jin-songxie@163.com



**FAN Bing-Quan** Professor and the director of Center of Research on Transports System, University of Shanghai for Science & Technology. His research interests include system engineering, complex transportation system analysis, network optimization, network traffic flow, transportation planning, and transportation impact analysis. E-mail: crts-usst@163.com



**Young Sam Lee** Received his Ph.D. degree in School of Electrical Engineering and Computer Science from Seoul National University, Seoul, Korea in 2003. His research interests include time delay systems, receding horizon control, robotics, and embedded systems. He is currently with the School of Electrical Engineering at Inha University, Incheon, Korea, since September 2004. E-mail: lys@inha.ac.kr

**YANG Jin** Received her B.S. and M.S. degrees from Nanjing Normal University in 2000 and 2003, respectively. Now she is a Ph.D candidate of the College of Science, University of Shanghai for Science & Technology. Her research interests include graph theory and combinational optimization. E-mail: yangjin\_78@hotmail.com